

First Release of Gauss–Legendre Sky Pixelization (GLESP) software package for CMB analysis

A.G. Doroshkevich¹, P.D. Naselsky^{2,3}, O.V. Verkhodanov⁴, D.I. Novikov^{5,1}, V.I. Turchaninov⁶,
I.D. Novikov^{1,2}, P.R. Christensen², L.-Y. Chiang²

¹ Astro Space Center of Lebedev Physical Institute, Profsoyuznaya 84/32, Moscow, Russia

² Niels Bohr Institute, Blegdamsvej 17, DK-2100 Copenhagen, Denmark

³ Rostov State University, Zorge 5, Rostov-Don, 344090, Russia

⁴ Special Astrophysical Observatory, Nizhnij Arkhyz, Karachaj-Cherkesia, 369167, Russia

⁵ Astrophysics, the Blackett Laboratory, Imperial College, London SW7 2AZ, UK

⁶ Keldysh Institute of Applied Math, Russian Academy of Science, 125047 Moscow, Russia

Abstract. We report the release of the Gauss–Legendre Sky Pixelization (GLESP) software package version 1.0. In this report we present the main features and functions for processing and manipulation of sky signals. Features for CMB polarization is underway and to be incorporated in a future release. Interested readers can visit <http://www.glesp.nbi.dk/> and register for receiving the package.

Key words. cosmology: cosmic microwave background — cosmology: observations — methods: data analysis

1. Introduction

The CMB temperature fluctuations on a sphere can be written as a sum over spherical harmonics

$$\Delta T(\theta, \varphi) = \sum_{l=2}^{\infty} \sum_{m=-l}^l |a_{lm}| e^{i\phi_{lm}} Y_{lm}(\theta, \varphi), \quad (1)$$

where $|a_{lm}|$ are the moduli of the spherical harmonic coefficients of the expansion and ϕ_{lm} are the phases defined in $[0, 2\pi]$. The angular power spectrum is defined as

$$C_l = \frac{1}{2l+1} \sum_{m=-l}^l |a_{lm}|^2 \quad (2)$$

and

$$D_l = \frac{l(l+1)}{2\pi} \frac{C_l}{T_0}. \quad (3)$$

where T_0 is the CMB temperature 2.726 K.

In this article, we report the first release of the Gauss–Legendre Sky Pixelization (GLESP) software package for the CMB analysis. The GLESP scheme (Doroshkevich et al. 2005) is based on the Gauss–Legendre polynomial zeros, allowing one to perform strict orthogonal spherical harmonic expansion of the CMB temperature anisotropies. The GLESP package has been tested on the following operating systems: RedHat Linux, SGI Irix and Solaris. Features for CMB polarization are under preparation.

2. Features in the GLESP package v1.0

2.1. Basic features for CMB analysis

The basic features of the GLESP package includes spherical harmonic analysis of a map, map synthesis from a given set of a_{lm} coefficients, and simulation of a Gaussian map from a given angular power spectrum C_l , or D_l .

cl2map

cl2map synthesizes CMB temperature maps from spherical harmonic coefficients a_{lm} . Inversely, it can decompose an input CMB temperature map into its spherical harmonic coefficients a_{lm} and/or power spectrum. If the input is a power spectrum C_l , or D_l , **cl2map** generates a Gaussian map of CMB anisotropies by assigning the a_{lm} mutually independent Gaussian-distributed real and imaginary parts, both with a standard deviation $\sqrt{C_l/2}$ at each l harmonic.

rsalm

rsalm convolves or deconvolves a map with a symmetric beam via

$$a'_{lm} = B_l a_{lm}, \quad (4)$$

where B_l is the expansion in Legendre polynomials of a symmetric beam. The symmetric beam can be input by reading in an ASCII file containing the profile of B_l or by providing the FWHM for a symmetric Gaussian beam, where $B_l = \exp[-\sigma^2 l(l+1)/2]$ and $\sigma = \text{FWHM}/\sqrt{8 \ln 2}$.

For deconvolution, a simple Tikhonov regularization scheme is applied via

$$a_{lm}'' = \frac{a_{lm}}{B_l + \alpha}, \quad (5)$$

where α is the regularization parameter.

f2fig

f2fig converts a GLESP map in FITS binary format into GIF (Graphic Interchange Format). **f2fig** offers users to put markers on the output figure. The markers can be input with one of the following 3 coordinate systems: in θ and ϕ of spherical polar coordinate system, in Galactic latitude b and longitude l of Galactic coordinate system and in right ascension (R.A.) and declination (Dec.) of equatorial coordinate system.

alm2dl

alm2dl reads a_{lm} and calculates the angular power spectrum C_l or D_l . It also provides the options in listing the amplitudes $|a_{lm}|$ or phases ϕ_{lm} defined in $[0, 2\pi]$.

2.2. Advanced features: map and a_{lm} manipulation

The package offers several advanced features that allow the users to manipulate pixelized maps or sets of a_{lm} .

difmap

difmap performs linear combinations of maps, map rotation, conversion of a map from Galactic to equatorial coordinate base. It can display simple map information such as pixel numbers and resolution, histogram, mean and variance, maximum and minimum temperature values and positions in (θ, ϕ) .

difalm

difalm performs arithmetic operations over a_{lm} such as addition, subtraction, multiplication and division by a factor. It also allows to swap the amplitudes and phases between two sets of a_{lm} . It can multiply/divide a_{lm} by given vectors $v(l)$.

mapcut

mapcut modifies a map in various ways. It can single out an area (either circular or rectangular) and set temperature values to zero in the area or outside the area. Furthermore, it can systematically remove or withhold several circular (or rectangular) areas by reading in a file containing those areas' positions and radii (or two corners). It can dissect a rectangular area from a map and output to a file in FITS format.

mapcut can also display temperature values of a GLESP map at given positions in one of the 3 coordinate systems: spherical polar, Galactic, and equatorial.

mappat

mappat performs the conversion between ASCII and FITS binary formats for a GLESP map. The derivative of this is that it allows one to input any patterns such as point source positions in ASCII and produce their whole-sky distribution.

2.3. Conversion between HEALPix and GLESP

The package also provides map conversion between HEALPix (Górski, Hivon & Wandelt 1999) and GLESP.

f2map

f2map performs repixelization of a GLESP map to HEALPix or to equidistant grid FITS Basic format. In the process of conversion to HEALPix, **f2map** can perform repixelization either using spline interpolation algorithm or direct mapping.

cmap

cmap performs repixelization of a HEALPix map to GLESP using spline interpolation for re-pixelization. On conversion to GLESP, the resolution is determined by the N_{side} value in HEALPix, otherwise, the resolution can be set according to user's input.

cmap can also display temperature values of a HEALPix map, or output the HEALPix map in ASCII format in 3 columns: θ , ϕ and temperature. **cmap** also reads the 2nd field of Binary Table Extension in HEALPix maps.

ntot

ntot calculates the total pixel number and size for both GLESP and HEALPix schemes. By giving a resolution, **ntot** calculates the parameters of the nearest allowed resolution for both schemes.

3. Objectives

3.1. Operation on a single map

Decomposing a map for its a_{lm}/C_l	c12map
Simulating a Gaussian map from given C_l	c12map
Displaying the map T_{max}/T_{min} , map resolution	
mean/variance	difmap
Map rotation	difmap
Arithmetic operations	difmap
Producing the histogram	difmap
Converting the map coordinate system to	
equatorial coordinates	difmap
Casting a mask on a map	difmap
Plotting the map and putting markers on the	
figure	f2fig
Displaying the temperature value at a given	
coordinate	mapcut
Truncating the temperature fluctuation to	
a given temperature range	mapcut
Removing or keeping specified areas from	
the map	mapcut
Map convolution and deconvolution	rsalm

3.2. operation on a single set of a_{lm}

Calculating the amplitude $ a_{lm} $	alm2dl
Calculating the phases ϕ_{lm}	alm2dl
Synthesizing a_{lm} for the map	c12map
Arithmetic operations on a_{lm}	difalm

Shifting phases	difalm
-----------------	--------

3.3. Operations over several maps

Linear combinations over maps	difmap
Cross correlation of 2 maps	difmap
Multiplication of 2 maps	difmap

3.4. Operation over several sets of a_{lm}

Linear combinations of a_{lm}	difalm
Swapping phases and amplitudes of 2 a_{lm}	difalm

3.5. Conversions

Converting GLESP FITS to HEALPix FITS	cmap
Converting HEALPix FITS to GLESP FITS	f2map
Converting FITS binary to ASCII	mappat
Converting/creating FITS binary from ASCII	mappat
Information on pixel number and size	ntot

4. Acknowledgment of using GLESP software package

Those who use the GLESP package for producing results should acknowledge in the publication. The reference should include the paper introducing the GLESP concept : Doroshkevich et al. International Journal of Modern Physics D, Vol 14, No.*, *** (2005).

5. Problems and Suggestions

For any technical issues, bugs, problems or suggestions, please send email to glesp@nbi.dk.

References

- Doroshkevich, A. G. et al. 2005, Int. J. Mod. Phys. D, Vol. 14, No. *, ***
- Górski, K. M., Hivon, E., & Wandelt, B. D., in “Evolution of Large-Scale Structure: from Recombination to Garching”, 1999 (<http://www.eso.org/science/healpix>).